

Technical Datasheet

- **Grade Name:** HDPE Injection 52B02
- **Categories:** Polymer, Thermoplastic, Polyethylene, High Density Polyethylene
- **Processing Methods:** Extrusion, Injection Molding, Rotational Molding
- **Applications:** Caps and closures for packaging, Bottles of Carbonated Water
- **Features:** Good impact strength, Excellent surface finish, Low warpage Plastic

Physical Properties			
Properties	Value	Unit	Test Method
MFI (190°C/2.16 KG)	2.3 ± 0.5	g/10min	ISO 1133
Density	0.952±0.002	g/cm ³	ISO 1183
Mechanical Properties			
Properties	Value	Unit	Test Method
Tensile Strength at Yield	20-27	MPa	ASTM D 638
Tensile Strength at Break	>14	MPa	ASTM D 638
Flexural Modulus	1100	MPa	ASTM D 790
Elongation at Break	1000	%	ASTM D 638
Izod Impact Strength, Notched	>50	J/m	ASTM D 256
Thermal Properties			
Properties	Value	Unit	Test Method
Vicat Softening Point	123	°C	ASTM D 1525
Stress cracking resistance (F50)	>30	hr	ASTM D 1693

Typical Properties: These values are not to be considered as product specifications.

This document is issued by the Company subject to its general condition of service printed overleaf. Attention is drawn to the limitations of liability identification and jurisdictional issues defined therein.

+981142434507

NO.9 Beshel Industrial City,
Shirgah, Mazandaran, Iran

