## Always there is a SOLUTION!





## **Technical Datasheet**

- o Grade Name: Acrilonitrile Butadiene Styrene (ABS) 150
- o Processing Methods: Extrusion, Injection Compression Molding
- $\circ$  Features: ABS 150 is one of the styrenic ter polymers (ABS) compound with  $3\pm 1$  % CaCo<sub>3</sub>. Exhibits, low shrinkage, and good dimensional stability. That is widely used in general injection molding applications.

Physical Properties			
Properties	Value	Unit	Test Method
MFI( 200°C/5 Kg)	1.8	g/10min	ASTM D-1238
<b>Bulk Density</b>	600	Kg/m³	ISO 1183
Mechanical Properties			
Properties	Value	Unit	Test Method
Tensile Strength at Yield	450	KGF/CM <sup>2</sup>	ASTM D 638
Izod Impact Strength, Notched	22	Kj/m <sup>2</sup>	ASTM D 256
Rockwell Hardness (23°C)	105	R Scale	ASTM D 785
Thermal Properties			
Properties	Value	Unit	Test Method
Vicat Softening Point	98	°C	ASTM D 1525

Typical Properties: These values are not to be considered as product specification.

This document is issued by the Company subject to its general condition of service printed overleaf. Attention is drawn to the limitations of liability identification and jurisdictional issues defined therein.

+981142434507



