

### Technical Datasheet

- **Grade Name:** EP440L COPOLYMER
- **Categories:** a medium flow heterophasic polypropylene copolymer with improved mechanical properties balance.
- **Processing Methods:** Injection molding
- **Applications:** Packaging, automotive and consumer goods industries Luggage, paint pails, buckets Containers, crates, batteries and large toys
- **Features:** High impact strength, High stiffness, Heterophasic copolymer

Physical Properties			
Properties	Value	Unit	Test Method
MFI( 230 °C/2.16 Kg)	6	g/10min	ISO 1133
Density	0.9	g/cm <sup>3</sup>	ISO 1183
Mechanical Properties			
Properties	Value	Unit	Test Method
Flexural Modulus	1400	MPa	ASTM D790
Tensile Strength at Yield	26	MPa	ASTM D638
Tensile Elongation at Yield	9	%	ASTM D638
Izod Impact Strength (notched) at 23 °C	170	J/m	ASTM D256
Izod Impact Strength (notched) at -20 °C	70	J/m	ASTM D256
Shore hardness (Shore D)	68	-	ISO 868
Thermal Properties			
Properties	Value	Unit	Test Method
H. D. T (0.46 MPa)	95	°C	ASTM D648
Vicat Softening Point (10 N)	152	°C	ASTM D1525
Accelerated oven ageing in air at 150 °C	360	h	ASTM D3012

Typical Properties: These values are not to be considered as product specifications.

This document is issued by the Company subject to its general condition of service printed overleaf. Attention is drawn to the limitations of liability identification and jurisdictional issues defined therein.

+981142434507

NO.9 Beshel Industrial City,  
Shirgah, Mazandaran, Iran

